

TeloPTT

ELEGANTLY SIMPLE, SUPERIOR AUDIO



TeloSystems
Bridging Communication Gap

Radio
Channel
Knob



Extremely
Loud Speaker



Textured PTT
Button



Radio
Design
Interface



TE300K



TE300



LTE/3G



3600mAh
Battery



GPS
Location



Android
OS



Optional



WiFi



Compact and
Handy

Dedicated Push-To-Talk Handheld

Instant communication to speed up the conversation.

Broadband connectivity to expand the worldwide coverage.

Specification

Items	Specifications
Frequency Band	Global Version GSM: B5, B8, B3 CDMA: BC0 WCDMA: B1, B4, B5, B8 TDD-LTE: B40 FDD-LTE: B1, B3, B5, B7, B8, B20, B28A, B28B American Version GSM: B5, B2, B8 WCDMA: B1, B2, B4, B5, B19 FDD-LTE: B1, B2, B4, B5, B7, B12, B17, B19, B28A, B28B
WIFI	IEEE802.11 b/g/n (2.4G & 5G)
Bluetooth	Bluetooth 4.0 with BLE
GPS	GPS, GLONASS, AGPS
Hardware	Specifications
CPU	MSM8909, 1.1GHz, Quad-Core
Memory	512M DDR3 + 4G ROM
Speaker	Ø36mm Max 2.0w
Battery	3600mAh
USB Port	USB 2.0 with Micro USB Type
Interface	M6 interface for Remote Speaker Microphone, Earpiece, External Camera
Sensor	Acceleration Sensor & Geomagnetic Sensor
Software	Specifications
Operating System	Android 6.0
Physical	Specifications
Dimensions (H x W x D)	121.5*56.5*28.5mm
Weight	Less than 220g
Protection Rating	IP67
Working Temperature	-20°C ~ 60°C
Storage Temperature	-30°C ~ 70°C

Accessories



RSM-35



TSR1-290



TSR1-8800

Reliable & Flexible

4/F, Chuangye Building, Seven-Star Park,
Yu'an 2nd Road, Bao'an District, Shenzhen, China

Tel: +86 755 86950766
Email: sales@telosystems.com

Fax: +86 755 86950708
Web: www.telosystems.com